

200 HP, 250 PSIG **Low or Ultra Low NOx Package Firetube Boiler**

Nationwide Boiler's 200 HP (6,900 lbs/hr) Hurst skid-mounted package firetube boiler is designed at 250 psig for low or ultra-low NOx applications, with your choice burner mounted upon receipt of order. The boiler / burner package will be fully piped and wired and include the following components:

- 3-Pass Wetback Boiler, 200 HP
- Oilon Low or Ultra Low NOx Burner (to be installed prior to shipment or at the jobsite)
- Complete Gas Train
- Hurst Stack Master Internal Stack Economizer
- NEMA 4 Control Panel w/ Siemens LMV Parallel Positioning Controls
- Valve Trim (safeties, blowdown, etc.)
- Steam Pressure Gauge
- Low Water Cutoffs (primary & auxiliary)
- Water Column & Site Glass
- Modulating Feedwater Control Valve
- High/Low Water & Flame Failure Alarms
- 6" Stack Thermocouple to Serve as High-Temp Safety Interlock
- Platform and Ladder Provisions to Boiler Shell
- Enhanced Durability with Double Thickness Boiler **Jacketing & Powder Coated Doors**
- Seismic Anchor Plates with Center of Gravity Calcs
- Meets UL / CSD-1 / NFPA 85
- **Electronic Operating Manual**



Fuel Consumption:

Natural Gas: 8,400 SCFH @ 5 psig

Typical Connection Sizes:

Main Steam: 4"-300# FLG Natural Gas: 3" NPT Blowdown / Drain: 1 1/4" NPT Feedwater: 1 1/2" NPT Chemical Feed: 1/2" NPT

Electrical Power Service Requirements:

480 VAC, 3 ph, 60 hz, 22 AMPS

Dimensions & Weights:

Length: 17' 2" Width: 7' 5" Height: 7' 8" Shipping Weight: 14,650 lbs Operating Weight: 49,400 lbs

Emissions Data (natural gas):

NOx (corr. to 3% O₂): As low as 21/2 ppm NOx

CO (corr. to 3% O₂): 30 ppm

Your Choice Burner for Low or Ultra Low NOx **Emissions Requirements**

42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com True Nationwide Coverage & Beyond. Representatives Located Worldwide.