



Rentals • Sales • Service
24/7 • (800) 227-1966

12,000 lbs/hr Atmospheric Feedwater System

Nationwide Boiler's skid-mounted 12,000 lb/hr Atmospheric Feedwater System includes the following:

- 360 Gallon Stainless Steel Tank on | Structural Steel Stand
- Tank Trim (including low water alarm and pump shutoff, gauge glass assembly, thermometer, sparge heater and manway)
- Water Inlet Modulating Control Valve Assembly
- Steam Inlet Self-Regulating Automatic Temperature Control Valve Assembly
- Condensate Return Connection w/ Strainer
- Common Pump Discharge Header
- Control Panel w/ Motor Starters and Disconnects
- Chemical Feed System for Tank Sulfite Injection
- Two (2) Grundfos Vertical Centrifugal Feedwater Pumps, 10 hp each, 24 gpm @ 258 psi



Connection Sizes:

Cold Water Make-up:	1¼ " NPT
Condensate Return:	1½" NPT
Common Drain Header:	2" NPT
Feedwater Discharge:	1½" NPT
Steam Inlet:	½" NPT

Electrical Power Requirements:

480 VAC, 40 amps

Dimensions & Weights:

Length:	6' 8"
Width:	5' 0"
Height:	8' 8"
Shipping Weight:	4,500 lbs
Flooded Weight:	12,000 lbs

Ask About Our **Green Solutions**

CataStakTM
 Ultra Low NOx Solutions

EconoStakTM
 Energy Saving Solutions

42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com

True Nationwide Coverage & Beyond. Representatives Located Worldwide.

** Actual equipment may differ from listed specification. Please consult Nationwide Boiler Inc. for additional details.*