



Rentals • Sales • Leasing
24/7 • (800) 227-1966

475 HP New In Stock Ultra Low NOx, 250 psig Skid-Mounted Boiler

Nationwide Boiler's ultra low NOx, 475 hp (16,388 lbs/hr) Superior skid-mounted boiler is designed at 250 psig pressure, firing natural gas. It is fully piped and wired and includes the following components:

- 475 hp Superior Package Firetube Boiler
- PowerFlame NVC11 Ultra Low NOx Burner
- 30 hp TEFC Blower Motor
- Compact XI-D Tube Design
- 3" Maxitrol 122-12 Gas Pressure Regulator (mounted)
- NEMA 4 Control Panel w/ Siemens LMV Parallel Positioning Controls
- Valve Trim (safeties, drain, etc.)
- Blowdown Valves (mounted & pre-piped)
- 6" Non-return Valve & 2nd Steam Gate Valve (loose)
- Single Point 480V Electrical Disconnect Connection w/ Step Down 115V Transformer
- 8" x 6" ASME Reducer Spool (loose)
- Modulating Feedwater Control Valve w/ 3 Valve Bypass (loose)
- Meets ASME Section I, Cal Code & CSD-1 Requirements
- Weatherproofed (except for freezing conditions)
- Operating Manuals on CD's



Fuel Consumption:

Natural Gas: 19,950 SCFH @ 10 psig regulated

Connection Sizes:

Steam: 6"-300# FLG
 Natural Gas: 3" NPT
 Blowdown/Drain: 1½" NPT
 Surface Blowdown: 1" NPT
 Feedwater: 2" NPT

Electrical Power Service Requirements:

480 VAC, 3 ph, 60 hz, 60 AMPS

Dimensions & Weights:

Length: 26' 0"
 Width: 8' 2"
 Height: 8' 9"
 Shipping Weight: 32,300 lbs
 Operating Weight: 47,650 lbs

Emissions Data (natural gas):

NOx (corr. to 3% O₂): 9 ppm
 CO (corr. to 3% O₂): 50 ppm

Ask About Our **Green Solutions**

CataStakTM
 Ultra Low NOx Solutions

EconoStakTM
 Energy Saving Solutions

42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com
 True Nationwide Coverage & Beyond. Representatives Located Worldwide.

* Actual equipment may differ from listed specification. Please consult Nationwide Boiler Inc. for additional details.