

Rentals • Sales • Service 24/7 • (800) 227-1966

180,000 pph Low NOx, 500 psig Skid-Mounted Boiler

Nationwide Boiler's low NOx 180,000 pph, 400 psig design (150-360 psig operating), saturated steam, skid-mounted package watertube Babcock & Wilcox boiler is set to burn natural gas or #2 oil. It is piped and wired and includes the following components:

- Low NOx Burner
- EconoStak Economizer
- Burner Management System
- Parallel Positioning Combustion Controls
- Forced Draft Fan & Motor
- Complete Fuel Train & Pilot Ignition System
- Water Column & Site Glass
- Steam Pressure Gauge
- Low-water Cutoffs
- Safety Valves
- Feedwater Stop & Check Valves
- Blowdown Valves
- Continuous Blowdown Metering Valve
- Chemical Feed Valve
- Steam Non-return Valve (loose)
- FGR Ductwork (loose)
- Stack (loose)
- NEMA 4 Electrical Enclosures
- Low NOx CataStak™ SCR System (optional)
- Weatherproofed (except for freezing)
- Meets FM, NFPA 85 & IRI Insurance Standards



Fuel Consumption:

Natural Gas: 217,000 SCFH @ 18 psi reg.

#2 Oil: 1530 GPH

Connection Sizes:

Chemical Feed:

Main Steam: 12"-300# FLG
Natural Gas: 6"-150# FLG
#2 Oil Supply: 1½" NPT
Feedwater: 4"-300# FLG
Bottom Blowdown: 1½"-300# FLG
Continuous Blowdown: 1" NPT

Atomizing Air / Steam: 1½" NPT / 1½" NPT

Instrument Air: ½" NPT
Water Column Drain: 1½" NPT

Electrical Power Service Requirements:

4160 / 2300 VAC, 3 ph, 60 hz, 400 HP Standard*

* Optional Voltage 50Hz Available

1/2" NPT

Boiler Dimensions & Weights:

Length / Width / Height: 56' 6" / 44' 6" / 16' 9"

Shipping Weight: 159,000 lbs Operating Weight: 171,500 lbs

Emissions Data (natural gas):

NOx (corr. to 3% O₂): 30 ppm CO (corr. to 3% O₂): 50 ppm

Ask About Our Green Solutions



42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com True Nationwide Coverage & Beyond. Representatives Located Worldwide.