



Rentals • Sales • Service
24/7 • (800) 227-1966

200 HP Superior Low NOx, 200 psig Skid-Mounted Boiler

Nationwide Boiler's low NOx, 200 hp (6,900 lbs/hr) Superior Model 10-X-750-S200-WBCF-GA2 skid-mounted boiler, designed at 200 psig pressure, firing natural gas or #2 oil. It includes the following components:

- 200 hp Wichita Firetube Boiler, 2-pass Wetback with XID Tubes
- Webster Low NOx Burner
- Complete Fuel Trains (loose, rack mounted)
- NEMA 4 Control Panel w/ Fireye BMS and Allen-Bradley CCS controls
- Valve Trim (safeties, blowdown, etc.)
- Steam Pressure Gauge
- Low Water Cutoffs (primary & auxiliary)
- Water Column & Site Glass
- Modulating Feedwater Control Valve
- High/Low Water & Flame Failure Alarms
- Meets UL / CSD-1 / NFPA 85
- Compliant with VA Boiler and Plant Safety Device Testing, Fourth Edition
- Electronic Operating Manual



Fuel Consumption:

Natural Gas:	8,400 SCFH @ 5 psig
#2 Oil:	60 GPH

Connection Sizes:

Main Steam:	6"-300# FLG
Natural Gas:	3" NPT
#2 Oil:	1" NPT
Blowdown / Drain:	1½" NPT
Feedwater:	2" NPT
Chemical Feed:	1" NPT

Electrical Power Service Requirements:

208/240/460 VAC, 3 ph, 60 hz, 30 AMPS

Dimensions & Weights:

Length:	20' 6"
Width:	9' 1"
Height:	7' 6"
Shipping Weight:	23,000 lbs
Operating Weight:	34,400 lbs

Emissions Data (natural gas):

NOx (corr. to 3% O ₂):	30 ppm
CO (corr. to 3% O ₂):	50 ppm

Ask About Our **Green Solutions**



42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com
 True Nationwide Coverage & Beyond. Representatives Located Worldwide.

* Actual equipment may differ from listed specification. Please consult Nationwide Boiler Inc. for additional details.