

200 HP **Ultra Low NOx, 250 psig Mobile Steam Plant**

Nationwide Boiler's ultra low NOx, 200 hp (6,900 lbs/hr) Mobile Steam Plant is an open-trailer system, designed at 250 psig pressure, firing natural gas. It is fully piped and wired and includes the following components:

- 200 hp Package Firetube Boiler
- Ultra Low NOx Burner
- Gas Pressure Regulator
- Control Panel
- Valve Trim (header, safeties, blowdown, etc.)
- Duplex Feedwater System/Condensate Return Tank
- **Duplex Water Softener**
- Chemical Feed System
- Blowdown Separator
- Stack (loose)
- **Operating Manuals**





Fuel Consumption:

Natural Gas: 8,400 SCFH @ 9 psig

Connection Sizes:

Main Steam: 6"-300# FLG Natural Gas: 3"-125# FLG Blowdown / Drain: 2"-300# FLG Condensate Return: 2" NPT

2" NPT (60-100 psig) Make-up Water:

Electrical Power Service Requirements:

480 VAC, 3 ph, 60 hz, 75 AMPS

Dimensions & Weights:

Length: 42' 8" Width: 7' 8" Height: 15' 9" Shipping Weight: 35,000 lbs Operating Weight: 50,000 lbs

Emissions Data (natural gas):

NOx (corr. to $3\% O_2$): 9 ppm CO (corr. to 3% O₂): 50 ppm

Ask About Our Green Solutions



42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com True Nationwide Coverage & Beyond. Representatives Located Worldwide.