



**Rentals • Sales • Service**  
**24/7 • (800) 227-1966**

## 800 hp Low NOx, 250 psig Skid-Mounted Boiler

Nationwide Boiler's low NOx, 800 hp (27,600 lbs/hr) skid-mounted Cleaver-Brooks firetube boiler, is designed at 250 psig pressure, firing natural gas or #2 oil, manufactured in 2005. It is fully piped and wired and includes the following components:

- Low NOx Burner
- Forced Draft Fan, Motor & Starter
- Complete Gas Train
- Oil System with Pump & Air Compressor
- Steam Pressure Gauge
- Dual Low Water Cutoffs
- Water Column & Site Glass
- Two (2) Safety Valves Set at 250 psig
- Feedwater Stop and Check Valves
- Bottom & Control Blowdown Valves
- Continuous Blowdown Metering Valve
- Control Panel w/ Combustion Control
- High/low Water and Flame Failure Alarm
- Pilot System w/ Electric Ignition
- Main Steam Non-return Valve (loose)
- Stack (loose)
- NEMA 3 Disconnect (unfused/mounted)
- Meets FM / IRI / NFPA 85
- Seismic Zone 3 & 4 Design
- EconoStak Economizer (optional)
- Low NOx CataStak™ SCR System (optional)
- Operating Manuals



### Fuel Consumption:

Natural Gas: 33,480 SCFH @ 10-25 psig  
 #2 Oil: 240 GPH

### Connection Sizes:

Main Steam: 8"-300# RF FLG  
 Natural Gas: 4"-150# FF FLG  
 #2 Oil Supply / Return: 1½" NPT / ¾" NPT  
 Feedwater: 2" NPT  
 Bottom Blowdown: 2" NPT  
 Continuous Blowdown: ¾" NPT  
 Flue Outlet: 27" OD FLG

### Electrical Power Service Requirements:

480 VAC, 3 ph, 60 hz, 125 AMPS

### Boiler Dimensions & Weights:

Length: 25' 3"  
 Width: 9' 5"  
 Height: 11' 2"  
 Shipping Weight: 60,500 lbs  
 Operating Weight: 83,500 lbs

### Emissions Data (natural gas):

NOx (corr. to 3% O<sub>2</sub>): 30 ppm  
 CO (corr. to 3% O<sub>2</sub>): 50 ppm

Ask About Our **Green Solutions**



42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / [www.nationwideboiler.com](http://www.nationwideboiler.com) / [info@nationwideboiler.com](mailto:info@nationwideboiler.com)

*True Nationwide Coverage & Beyond. Representatives Located Worldwide.*

\* Actual Equipment may differ from listed specification. Please consult Nationwide Boiler Inc. for additional details.