

Rentals • Sales • Service 24/7 • (800) 227-1966

90,000 pph, 250 psig Indeck D-Type Package Watertube Boiler

One (1) 90,000 PPH 250 psig saturated steam, package watertube boiler is set to burn natural gas (#2 oil is optional). It was originally built in 2012 and includes the following components:

- Low NOx Burner
- Economizer
- Burner Management System
- Parallel Positioning Combustion Controls
- Forced Draft Fan, Motor & Starter
- Complete Fuel Train & Pilot Ignition System
- Water Column & Site Glass
- Steam Pressure Gauge
- Low-water Cutoffs
- Safety Valves
- Feedwater Stop & Check Valves
- Blowdown Valves
- Continuous Blowdown Metering Valve
- Chemical Feed Valve
- Single Element Feedwater Regulator with Pre-piped 3-Valve Bypass
- Steam Non-return Valve
- FGR Ductwork (loose)
- Stack (loose)
- NEMA 4 Electrical Enclosures
- Separate Fuel Oil Skid for #2 Oil Firing (optional)
- Ultra Low NOx CataStak™ SCR System (optional)
- Weatherproofed (except for freezing)
- ASME, FM, NFPA 85 & GE Gap Insurance Compliant
- Electronic Operating Manuals



Fuel Consumption:

Natural Gas: 109,900 SCFH @ 15-25 psi reg.

#2 oil (optional) 700 GPH

Connection Sizes:

Main Steam: 8"-300# FLG Natural Gas: 4"-150# FLG

#2 oil supply/return 11/4 "-150# FLG / 3/4"-150# FLG

Feedwater: 3"-300# FLG Bottom Blowdown: 1½"-300# FLG

Continuous Blowdown: 1" NPT
Chemical Feed 1" NPT
Atomizing Steam: 1"-150# FLG
Instrument Air: ½" NPT
Water Column Drain: ¾" NPT

Electrical Power Service Requirements:

480 VAC, 3 ph, 60 hz, 250 AMPS

Dimensions & Weights:

Length / Width / Height: 32' 7" / 11' 5" / 14' 6"

Shipping Weight: 105,000 lbs Operating Weight: 136,500 lbs

Emissions Data (natural gas):

NOx (corr. to $3\% O_2$): 30 ppm CO (corr. to $3\% O_2$): 50 ppm

Ask About Our Green Solutions



42400 Christy Street / Fremont, CA 94538 / (510) 490-7100 / www.nationwideboiler.com / info@nationwideboiler.com True Nationwide Coverage & Beyond. Representatives Located Worldwide.